

Technical Data Sheet

577



763-582-1140

800-966-2909

www.seacole.com

13505 Industrial Park Blvd.
Plymouth, MN 55441

577

Ferrous Metal Safe, In-Process Rust Inhibitor

Product Description

577 is a liquid inorganic rust inhibitor designed for treatment of steel and iron parts. 577 works by reacting with the surface of the metal and passivating it. There does not need to be any residual 577 left on the parts surface to provide rust protection. Parts can be welded, painted, plated or assembled without the additional step of removing the rust inhibitor.

Performance Features

- Provides In-Process Rust Protection to Iron or Steel Parts and to Steel Media During Deburring Operations
- Provides Rust Protection For Short-Term Storage After Cleaning or Mass Finishing of Iron or Steel Parts
- Does Not Require Parts To Be Re-Cleaned Before Painting Or Heat Treatment
- Compatible With Most Alkaline Compounds When Simultaneous Use Is Required

Physical Specifications

Physical State	Liquid
Appearance	Green
pH (use dilution)	9.5

Equipment Requirements

577 is safe for use in all standard mass finishing or process parts cleaning systems. Operation of equipment should be done in accordance with the equipment manufacturer's instructions.

Product Make-Up

577 is a concentrated industrial rust inhibitor. Dilute to specified strength concentrations.

Concentration and Application Methods

In-Process / Short Term

For maximum rust protection, use along with an alkaline cleaning or deburring compound or in the final rinse section after cleaning, deburring, descaling or burnishing operations. Add 1 - 8 fl oz. of 577 per gallon of water depending on operating conditions and degree of protection desired; 2 fl oz. per gallon is a typical starting point.



Companion Products

See Seacole's 500 Mass and Metal Finishing Series and Seacole's Spraydet Product Line

Safety and Handling

Read and understand this products SDS before handling.

Waste Treatment

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations. Contact Seacole for specific details and/or further waste treatment recommendations.

Ordering Information

577 is available in 1 liter bottles, 30 gallon drums, and 55 gallon drums.

Customer Notice: Seacole strongly encourages its customers to review their manufacturing processes and their applications of Seacole products from the standpoint of human health and environmental quality to ensure that Seacole products are not used in ways for which they are not intended or tested. Seacole personnel are available to answer your questions and to provide reasonable technical support. Seacole product literature, including safety data sheets, should be consulted prior to use of Seacole products.



763-582-1140
800-966-2909

Copyright ©2018 Seacole-CRC, LLC. All rights reserved. All Seacole logos are registered trademarks of Seacole-CRC. All other marks are the property of their respective owners. The information and specifications in this data sheet are subject to change without notice. This product may be exported from the US only in accordance with the Export Administration Regulations established by the U.S. Department of Commerce, Bureau of Industry and Security.